

PRODUCT FEATURES

- » Using High-performance processor 5.0 mega pixel CMOS imaging sensor
- » Supports 5MP (2592*1944) 15fps monitoring
- » Using Linux embedded OS, low power consumption, steady and credible
- » Using H.265+, H265 encoding, high compression ratio and lower stream
- » Supports ICR automatic switchover, achieve round-the-clock monitoring
- » Supports network interrupt, IP conflict, motion detection, video blind smart alarm
- » Supports abnormal automatic recovery and network interrupt auto-reconnect functionality
- » Supports watermark encryption ,prevent data from being tampered;
- » Support DC12V/POE, easy to install
- » Supports IP66 waterproofing grade
- » Supports anti-static and surge
- » Supports ONVIF protocol access
- » Infrared distance of 35 meters
- » Provide SDK development kit, access to other video management platform



SPECIFICATIONS

Image sensor	1/2.5" CMOS
Max resolution	2592*1944
Electronic shutter	Manual / automatic adjustment, 1/25 sec to 1/10000 sec
Minimum illumination	0.1Lux@F1.2(color mode); 0.01Lux@F1.2
Day & Night	Color/black and white/IR-CUT/automatic
Scanning method	Progressive scan
WDR	Not support
SNR	≥50dB
Gain Control	Automatic
White Balance	Automatic
BLC	Support
Infrared distance	20-35m
Focal length	2.8-12mm
Type	Manual variable focal lens
Iris control	Variable iris
Interface	φ14
Video compression	H.265+/H.265/H.264
Video bit rate	8kbps~32Mbps, Customizable
Video frame rate	Main Stream (2592*1944@15fps), secondary stream (D1@25fps)
Image settings	Brightness / contrast / sharpness /
OSD superimposing	Time; channel name; Position; Picture Manual recording, time recording
Recording mode	Recording descending order of priority: manual / timing
User management	Support multi-levels user administration
Restore the default	Support for a key to restore the default configuration
Alarm and Data	Support FTP, E-mail Browser, CMS
Privacy masking	Support
Motion detection	Support
Network interface	1 RJ45 10/100M Ethernet interface
Network protocol	Support/TCP/IP/HTTP/RTSP/FTP/PPPOE/RTCP/SNMP/DHCP/DDNS/NTP/UPnP/SNMP
Power supply	DC12V/POE
Power consumption	12W Max
Working temperature	-20°C~+55°C
Working humidity	≤95%
Protection class	IP66
Shell Material	Metal
Mounting	Wall/ceiling

DIMENSIONS

